



International Waxes Inc.

AstorLite® J50
Candle Wax & Additive
Product Data Sheet

Product Description	AstorLite® J50 is a soft white, opaque wax specially designed for jar / container candles. Its cohesive strength and low shrinkage allow it to adhere to the container. Using AstorLite® J50, jar/container candles can be made with a single filling with no top-off necessary.		
Typical Properties and Characteristics	Test Description	ASTM Method	Typical
	Congealing Point, °F	(ASTM D-938)	124 – 132°F
	Penetration @ 25°C	(ASTM D-1321)	86 – 110 dmm Min
	Drop melting Point	(ASTM D-127)	128 - 136°F
	Color, Saybolt	(ASTM D-156)	+8 Min
Product Form and Packaging	AstorLite® J50 is offered in slabs of approx 10 lbs, packed in 50 lb. cartons.		
Storage and Handling	AstorLite® J50 should be stored in a cool, dry place where the temperature does not exceed 30°C/86°F.		
Health & Safety	See MSDS		
Customer Service	USA	Canada	
	85 Old Eagle School Road P.O. Box 384 Wayne, PA 19087	50 Salome Drive Toronto, Ontario M1S 2A8	
	Toll Free: 1-800-852-6537 Telephone: (610) 687-9030 Fax: (610) 254-8548	Toll Free: 1-800-561-3509 Telephone: (416) 293-4151 Fax: (416) 293-5858 Email: cstoronto@igiwax.com	
Website	www.igiwax.com		

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.